

Floordefend Top-Mat

Protectapeel Floordefend Top-Mat is a weather and skid resistant protective top-mat, designed for use with Protectapeel products. The Floordefend system is a 2 part process, using a Protectapeel product as the base-coat, then the Floordefend top-mat is applied. This system will protect virtually all non-porous surfaces including, concrete flooring, tiles, glass, and metals from damage for up to 9 months externally. The Floordefend system protects against damage such as scratches, surface abrasions, spillages, overspray, dust and dirt transfer.

Colour - Floordefend top-mat - Grey. Floordefend top-mat can be over painted for walkway markings.

Health & Safety - The Floordefend top-mat is non-hazardous. The Protectapeel base-coat product compound is non-toxic and non-flammable in the wet state. The dry film waste may be disposed of as low hazard. Please see separate Safety Data Sheet (SDS)

Application - Apply the suitable Protectapeel base-coat product according to its TDS, then immediately press the Floordefend top-mat into the Protectapeel base-coat using a dry roller.

Please see Floordefend Application Guide for more detailed instructions.

Do not apply in wet or freezing conditions and protect from rainfall.

Repair - If the protective coating rips, repair by lifting the ripped patch and apply a fresh coat of protectapeel base-coat to the underside and reseal. Alternatively, cut away the damaged area and apply a fresh base-coat and Floordefend top-mat.

Drying Time - Ensure you will receive at least 6 hours of clear weather in order for the Floordefend system to dry adequately. Cordon off the area from foot or vehicle traffic for at least 3 hours.

Surfaces – Virtually all non-porous surfaces including concrete, tiles, glass, PVC, metals & painted surfaces.

Coverage - 1m² of Floordefend top-mat will cover 1m². When using Protectapeel Multisurface as a base-coat 1kg will cover 3m² at a WFT of 350 Microns.

Removal - The Floordefend system can be easily removed by hand peeling. Do not remove in freezing conditions as the film may be brittle.



External Weather Resistance - The Floordefend system offers protection for up to 9 months externally.

Storage - Store in a dry place away from heat and prevent from freezing.

Clean Down - Clean rollers in water immediately after use if they have come in contact with the Protectapeel base-coat.

General Note: It is important that this product is thoroughly evaluated under production conditions before being commercially adopted (Such an evaluation should incorporate a reference to ageing). The above recommendations are made in good faith for the guidance of users and are without liability. Any queries should be referred to our Technical Sales Department.